VEGETABLE CUTTING MACHINESRG100 • RG200 • RG250 • RG350 • RG400





THE GREATEST VERSATILITY AND PRODUCTIVITY IN A VERY COMPACT SPACE

The **RG Vegetable Cutting Machines** offer the perfect solution to the following problems: reduction of preparation times, a perfect presentation of processed vegetables, the need for a wider and more varied menu, the observance of high hygienic standards.

Thanks to their operating speed, versatility and easy use, the Nilma **RG Vegetable Cutting Machines** can slice, chop, dice and shred not only vegetables and roots, but also fresh and dried fruit, bread and cheese

All this taking little space and in a very short time. The exclusive feed hoppers make the introduction

of all products extremely simple, allowing a clean and precise cut.

Thanks to the wide range of cutting tools, it is always possible to obtain the required shape and thickness, ensuring a perfect presentation. This also applies to soft products like tomatoes.

All these features make the **RG Vegetable Cutting Machines** an ideal equipment for the kitchens of commissaries, hotels, restaurants and food processing facilities, where the quality of the results is very

important, as well as the labour saving, the versatility of use, the relia—bility and the safe operation.



LA SCIENZA DELLE GRANDI CUCINE

VEGETABLE CUTTING MACHINES

RG100 • RG200 • RG250 • RG350 • RG400

>>)

THE FEATURES

- Housing made of anodized aluminium with mechanical parts made of 18/10 stainless steel.
- · Safety devices.

- · Transmission: geared motor.
- Cutting tools made of alluminium alloy, with blades made of treated stainless steel.
- · Double speed for the RG 400 model.

>>)

TECHNICAL DATA

	RG 100	RG 200	RG 250	RG 350	RG 400		
Electric	230 V	230 V	230 V	400-230V	230 V-3ph 50Hz		
connection	1ph 50Hz	1ph 50Hz	1ph 50Hz	3ph 50Hz	400 V-3ph 50Hz		
Power	0,21 kW	0,37 kW	0,37 kW	0,75 kW	0,9/1,5 kW		
Weight	16 kg	18,5 kg	21 kg	32 kg	55 kg		
Hourly capacity	300 kg	400 kg	480 kg	720 kg	2400 kg		

Technical drawings 385 475 80 RG250 RG250 RG250 RG350 RG350








>>

A WIDE RANGE OF CUTTING TOOLS



wall-rack

A Standard slicer

- · slices firm products, such as root vegetables.
- dices in combination with type G1 dicing grid, in the heights 4.5-6-10 mm, and with type G2 dicing grid, in the heights 15 and 20 mm.

B Dicing cutter

• in combination with type G1 dicing grid, from 12.5 x 12.5 mm upwards, dices root vegetables (potatoes also precooked, but hard), cabbage, etc.

Crimping slicer

· for ripple slicing of root vegetables

D2 Fine cut slicer, two blades

- slices firm and soft products, such as potatoes, onions, cucumbers, mushrooms, etc.
- shreds cabbage

D1 Fine cut slicer, one blade

- slices firm and soft products, also juicy, such as root vegetables, tomatoes, lemons, bananas, mushrooms, etc.
- · shreds lettuce.
- in combination with dicing grid from 10 x 10 mm upwards, the 4 mm slicer chops onions.
- the 4, 6 and 10 mm slicers dice in combination with type G1 dicing grids.
- the 14 and 20 mm slicers dice in combination with type G2 dicing grids.

Julienne cutter

- · for julienne cut
- · 2.5 x 6 for shredded cabbage.
- 10 x 10 for curved french fry potatoes

G Dicing grid

 dices root vegetables, potatoes, cabbage, fruit, etc., in combination with the suitable standard and fine cut slicers.
 N.B.: Type G1 dicing grids cannot be combined with 14, 15 and 20 mm slicers – see dicing grids (G2)

G2 Dicing grids

 dice root vegetables, potatoes, fruit, etc, in combination with 14 and 20 mm fine cut slicers, and with 15 and 20 mm standard slicers.

H French fry grid

 cuts straight potatoes (french fries), in combination with the 10 mm fine cut slicer.

Raw food grate

- · grates raw potatoes, dry bread, almonds, nuts, etc.
- the 6 or 8 mm are commonly used for grating pizza cheese.
- · the 8 mm is used for shredding cabbage

Fine grater

· grates raw potatoes, radish, dry bread, hard cheese, etc.

>>

CUTTING SIZES (mm)

RG100	A 8-10	B 12,5	4,5	D2	3-4-6- 10-14	F		G1		G2	н	К
						2x2 2x6 4,5x4,5 8x8	2,5x2,5 3x3 6x6 10x10	7,5x7,5 15x15	10×10 20×20			1,5-2- 3-4,5- 6-8-10
RG200 RG250	6-8-10-20	12,5	4,5	0,5-1 1,5-2	3-4-6- 10-14	2x2 4,5x4,5 8x8	2,5x2,5 6x6 10x10	6,25x6,25 10x10 15x15	7,5x7,5 12,5x12,5 20x20		10	1,5-2-3 4,5-6-8 -10
RG350 RG400	4,5 6-10 15-20	12,5	4,5	0,5-1 1,5-2-3	4-6-10 14-20	2X2 2,5x6 6x6	2,5X2,5 4,5x4,5 10x10	6,25x6,25 10x10 15x15 25x25	7,5x7,5 12,5x12,5 20x20	15x15 20x20 25x25	10	1,5-2-3 4,5-6-8

FIVE MODELS FOR 100 USES

To slice, dice, grate, chop, shred, etc. vegetables, fruit, mushrooms, nuts, almonds, dry bread, cheese, all of this with each model!

suitable for 400 portions

RG 200

about 200 to

floor machine frame

collecting trolley

RG 400

suitable for more than 1000 portions and for food processing industries

pneumatic

push feed ttachment

ACCESSORIES

>> FOR ALL MODELS

- Cutting tools
- Wall-rack for cutting tools. It saves space and prevents blade damages.

>> RG100 and RG200:

Pipe insert incluse pestle (pict.1)

>>) RG250:

• Floor machine frame (pict.2)

>>) RG350:

- Floor machine frame (pict.2)
- Feed hopper, made of 18/10 stainless steel, with safety devices, for continuous cutting of large quantities of round products, such as potatoes, onions, tomatoes, nuts, dry bread (pict.3).
- Product collecting trolley, made of 18/10 stainless steel, with GN 1/1 container, h. 200 mm. (pict.4)

>> RG400:

- Product collecting trolley, made of 18/10 stainless steel, with GN 1/1 container, h. 200 mm. (pict.4)
- Feed hopper, made of 18/10 stainless steel, with safety devices, for continuous cutting of large quantities of round products, such as potatoes, onions, tomatoes, nuts, dry bread (pict.5).
- · Feed cylinder, made of anticorodal, to be used with the following accessories:
- -4-tube insert (one tube with Ø 45 mm, one tube with Ø 63 mm and two tubes with Ø 73 mm), for the cutting of carrots, cucumbers, leeks, celery and peppers (pict.6).
- -Manually-operated push feed attachment (max. diameter for product introduction: 200 mm, cylinder volume: 7 l.) for the cutting of cabbage, carrots, lettuce, cheese (picture 7).
- Pneumatic push feed attachment, made of 18/10 stainless steel, with 3 speeds and pusher with adjustable pressure (pict.8).
- Electro-compressor for pneumatic insert

RG 100 suitable for about 50

to 200 portions

RG 250

suitable for about 400 to 600 portions



suitable for about 600 to 1000 portions



manually-

product

operated push

feed attachment

feed hopper

